




【XEK 电动宽叉腿堆垛车】
XEK Electric Straddle Stacker

ISO 9001 CE



- 进口他励电控
Imported seperately excited electric control
- 再生制动功能
Regenerative braking function
- 德国Frei原装手柄
Frei tiller ,original device of Germany
- 蓄电池侧位装卸
Sideways battery exit
- 宽视野门架
Widen mast views
- 可选用进口交流电控
Optional imported AC electronic controller



XEK电动宽叉腿堆垛车技术参数

XEK Electric Straddle Stacker Technical Data



特性 Identification	1	产品型号	Product model designation			XEK15A	XEK15B
	2	驱动形式	Drive unit			电动	Electric
	3	驾驶方式	Operator type			站驾式	Standing
	4	额定载荷	Load capacity	Q	kg	1500	1500
	5	载荷中心	Load center	C	mm	600	600
	6	后悬距	Load distance,centre of drive axle to fork back		X	mm	490
	7	轴距	Wheelbase		Y	mm	1340
重量 Weight	1	自重(不含电池)	Truck Weight(without battery)		kg	781	761
	2	桥荷 满载(前/后)	Axle loading, loaded(front/rear)		kg	911/1620	903/1607
	3	桥荷 空载(前/后)	Axle loading, unloaded(front/rear)		kg	690/340	677/334
轮子 Wheel	1	轮胎	Tyres			聚氨酯轮	Polyurethane
	2	驱动轮尺寸	Driven wheels size		mm	Φ250×80	Φ250×80
	3	承载轮尺寸	Loaded wheels size		mm	Φ80×70	Φ80×70
	4	平衡轮尺寸	Balance wheels size		mm	Φ125×50	Φ125×50
	5	轮子数量(前/后)(x=驱动轮,front/rear(x=driven wheels)	Wheels number, front/rear(x=driven wheels)			1x-2/4	1x-2/4
	6	前轮距	Tread,front		mm	690	690
	7	后轮距	Tread,rear			1394/1084	1394/1084
基本尺寸 Dimensions	1	总高(货叉最低时)	Height,mast lowered			1750	1750
	2	自由提升高度	Free lift		h2	mm	/
	3	起升高度	Lift height		h3	mm	2500
	4	最大高度(货叉最高时)	Maximum height,mast extended		h4	mm	2965
	5	货叉离地高度(最低时)	Forks height,lowered		h5	mm	66/40
	6	操作手柄离地高度(最大/最小)	Height of tiller in drive position(max/min)		h6	mm	1350/985
	7	总长	Overall length		L1	mm	2070/1870
	8	货叉前端面至前部距离	Length to face of forks		L2	mm	925
	9	底腿内宽	Inside width at the end of leg		b2	mm	1270/960
	10	总宽	Overall width		b1	mm	1518/1208
	11	货叉尺寸(锻打)	Fork dimensions(Forging)		S/e/l	mm	100/40/950
	12	货叉外宽(固定可调)	Maximum forks width		b3	mm	580、200-800
	13	最小离地间隙	Minimum ground clearance		m	mm	30
	14	直角堆垛通道宽度,托盘800X1200(1200沿货叉边) Aisle width for pallets 800X1200 lengthways			Ast	mm	2350
	15	转弯半径	Turning radius		Wa	mm	1610
性能 Performance	1	行驶速度 满载/空载	Travel speed Loaded/unloaded		km/h	5、2/6	4/5
	2	提升速度 满载/空载	Lift speed Loaded/unloaded		mm/s	90/120	90/120
	3	下降速度 满载/空载	Lowering speed Loaded/unloaded		mm/s	125/80	125/80
	4	最大爬坡能力 满载/空载	Max gradeability Loaded/unloaded		%	5/8	5/8
	5	制动方式	Service brake			电磁制动	Electromagnetic brake
电机 Electric Motor	1	驱动电机功率	Drive motor rating		kw	1.2	1.2
	2	提升电机功率	Lift motor rating		kw	2.2	2.2
	3	蓄电池电压/容量	Battery voltage /capacity		V/Ah	24/210	24/210
	4	蓄电池重量	Battery weight		kg	250	250
其他 Others	1	控制方式	Control unit type			场效应管控制	MOSFET control
	2	整车噪音	Sound level		dB (A)	<70	<70

高度参数 Height Data

1	总高	Overall height	h1	mm	1980	2180	1750	2000	2150	2350	2500	1955	2055
2	自由提升高度	Free Lift	h2	mm	1600	1800	/	/	/	/	/	1390	1490
3	起升高度	Lift Height	h3	mm	1600	1800	2500	3000	3300	3700	4000	4200	4500
4	最大高度	Maximum height	h4	mm	1980	2180	2956	3465	3765	4165	4465	4679	4979

